

3POE Output+1POE input 100m

Distance POE Extender



- ❖ 3*10/100Mbps POE port to output, 1*10/100Mbps port to input
- ❖ 100m Distance
- ❖ Support IEEE802.3AF/AT
- ❖ POE In: 44V-57V/30W;
- ❖ POE Output (1-3) : 44-57V /25W
- ❖ All port supported by MDI/MDIX auto flip and self negotiation
- ❖ Supply 4 10/100Mbps adaptive high speed forwarding data packet non-lost port.
- ❖ Each port max. power supply reached 8W.

Application:

- ❖ Wireless Access Point
- ❖ IP Camera
- ❖ IP Phone
- ❖ Computer Networks

Product	POE Extender
Model	HR-POE013
POE Port	IEEE802.3AF/AT Standard
Output Power	8W/Per port
Power input Pin	1/2+, 3/6-, 4/5+, 7/8-
Power output pin	1/2+, 3/6-
Whole Power	≤25W
POE Protocol	IEEE 802.3af/IEEE 802.3at
Power Distance	≤100m
Network Standard	IEEE 802.3, IEEE802.3u, 802.3x, 802.3af/at
Network Medium	10/100BASE-TX:5 class and above non shielded twisted pair
Data Distance	≤100m
Switch Capability	1Gbps
Forwarding Rate	10BASE-tx:14880pps/port 100BASE-tx: 14800pps/port
MAC Address	MAC address table 1K
Port Function	Power priority mechanism, fast and forward, MAC automatic learning and aging IEEE802.3X Full-duplex and mode and backpressure for Half-duplex mode
Working Environment	Working temperature: -10° -- 55° C
Weight	0.055kg
Size	82mm*52mm*23mm (L*W*H)